

Controller

CAREL Touch Screen Control 4.3





	Cabinet	Galvanized sheet sand ash+matte black spray coating	
Main parts	3 way valve	DN25	
	Electric heater	3kW/220-240V~	3kW/380V~
	Expansion tank	5L	3KW/300V~
	Buffer tank+Hot water tank (2 in one)	60L +150L	
	Coil pipe (SUS304)	DN32*15m	
	AC contactor (A)	32A (Explosion proof relay)	
	Controller	Carel Touch Screen controller	
	Other parts	Built in drain valve and exhaust valve	
	Package	Wooden	
Parameters	Power supply (V)	220-240~	380-420 2N~
	Connection size for hot water tank pipes	Cold water outlet DN15, hot water outlet DN20/outer thread	
	Connection size of heat pump/buffer		
	water tank	DN25/outer thread	
	Exhaust pipe size	DN15/Inner thread	
	Elctric heater	Buffer tank 3kw, hot water tank 3KW	
	Current (A)	13.6A+13.6A	7.8A+7.8A
	Max water temp	75°C	
	Net zize (mm)	585*630*1865mm	585*630*1865mm
	Package size (mm)	670*715*2045mm	670*715*2045mm
	Suitable model	CGK030V4P、CGK040V4P、CGK050V4P CGK060V4P、CGK-030V4P、CGK-040V4P、 CGK-050V4P、CGK-060V4P	CGK-030V4P、CGK-040V4P、 CGK-050V4PCGK-060V4P、
Advantage		*Efficient Heating *Upgraded Double Safety Protection, *Equipped with Dual Dry-Burning Protection and Temperature Control Protection * Dual Temperature Zone Control *Zero Cold Water Control *Support for Solar Water Heater Connectivity	