R290 Heat Pump Kit Specification





	Model	CGH06-C	CGH-06-C
Main Configuration	Sheet Metal	Frosted Grey	Frosted Grey
	3-Way Valve	DN25	DN25
	Multifunctional Filter	Caleffi multifunctional exhaust valve (With microbubble exhaust function, impurity filtering function, sewage discharge function, magnet adsorption function for iron filings, gas collection function, and water pressure display function)	Caleffi multifunctional exhaust valve (With microbubble exhaust function, impurity filtering function, sewage discharge function, magnet adsorption function for iron filings, gas collection function, and water pressure display function)
	Electric Heater	Pipe type 3kW/220-240~	Pipe type 3kW/380-420 2N~
	Expansion Tank (L)	5	5
	AC Contactor (A)	32A (Explosion-proof Relay)	32A (Explosion-proof Relay)
	Package	Splint/Carton	Splint/Carton
Parameters	Water Pipe Connection Size	DN25 (Inner thread)	DN25 (Inner thread)
	Exhaust Pipe Size	DN15 (Inner thread)	DN15 (Inner thread)
	Power Supply (V)	220-240~	380-420 2N~
	Power	3kW	3kW
	Current (A)	14.4	6.3
	Net Weight (kg)	36	36
	Gross Weight (kg)	41	41
	Splint Gross Weight (kg)	51	51
	Net Dimension (mm)	565*200*673	565*200*673
	Packing Dimension (mm)	650*285*750	650*285*750
	Splint Packaging Dimension (mm)	625*260*810	625*260*810
	Applicable Models	CGK030V4P、CGK040V4P、 CGK050V4P、 CGK060V4P、CGK-030V4P、CGK- 040V4P、CGK-050V4P、CGK-060V4P	CGK-030V4P、CGK-040V4P、 CGK-050V4P、CGK-060V4P、

Note: If the 380 model uses the CGH06-C heat pump kit, please pay attention to whether the power supply can withstand the current of the heat pump kit. Connecting cables, air circuit breakers, etc. require additional configuration by the user.

Main Components					
Schneider AC Contactor	Schneider AC contactor		GCALEFFI Hydranic Solutions Filter		
	Expansion Tank 5L Expansion Tank		Electric heater (3kw)		
	3 way valve				